





Used to measure the moisture level in sawn timber (also cardboard, paper) and hardened materials (plaster, concrete and mortar). It displays the moisture level in the material straightaway.

DT-125 MOISTURE METER

- I Measures moisture content in wood and construction material, also cardboard & paper
- I Auto Power Off
- I Battery Check function
- I Auto Power On

DT-125 Moisture Meter



General Specifications

Measuring principle	Electrical resistance	
Electrode length	8 mm	
Electrodes	Integrated, replaceable	
Measuring range	Wood 6 - 44 %	
	Material : 0.2 – 2.0 %	
Display Accuracy	Wood : ±1 %	
	Material : ±0.05 %	
Auto power OFF	After approx. 15 minutes	
Battery	3 × Cr 2032, replaceable	
Housing material	Impact-proof plastic housing	
Ambient temperature	0 - 40°C	
Ambient Relative humidity	0 - 85%RH	
Dimensions	130 × 47 × 25 mm	
Weight	approximately 100g	
Warranty	1 year	

Accessories

Battery, Test Certificate and Instruction Manual.

Calibration and battery check



AAYUSH ELECTRICALS & INSTRUMENTATION ISO 9001-2015 CERTIFIED COMPANY Office Address : # 1, 1st Main, 2nd Cross, Maruthinagar, Bengaluru, Karnataka - 560 026. India Factory Address : #18,4th A Main Road, Bahubali Nagar, Jahalli Village, Bengaluru - 560013 Email : sales@aayushei.com / marketing@aayushei.com / accounts@aayushei.com Web : www.aayushei.com , Mob : +91 88922 55555 / 96639 82272/ 88922 77777



QMS/019303/1120