



The Temperature & Humidity
Datalogger is designed with a high
accuracy Temperature & Humidity
Sensor. This datalogger is provided
with features of high accuracy, fast
response and stability. It is widely used
for monitoring and collecting data of
environment temperature and humidity.



## **DT-172**

# TEMPERATURE AND HUMIDITY DATALOGGER

- I Memory for 32,000 readings (16000 temperature and 16,000 humidity readings)
- I LCD to show some logging information easily
- I Freely selectable measurement cycle from 1 sec. to 24h
- I Download collected data through PC's USB
- I Max / Min display
- I Alarm display if user-defined maximum/minimum values are exceeded
- I Analysis software used to view graph for logging data



### **Technical Specifications**

Relative Humidity	Overall Range	0 to 100%
	Accuracy (0 to 20 and 80 to 100%)	±5.0%
	Accuracy (20 to 40 and 60 to 80%)	±3.5%
	Accuracy (40 to 60%)	±3.0%
Temperature	Overall Range	-40 to 70°C (-40 to 158°F)
	Accuracy (-40 to -10°C and +40 to +70°C)	±2°C
	Accuracy (-10 to +40°C)	±1°C
	Accuracy (-40 to 14 and 104 to 158°F)	±3.6°F
	Accuracy (+14 to 104°F)	±1.8°F
Resolution	0.1%RH, 0.1°C	
Memory	32700 values	
Measuring cycle	1s to 24h	
Analysis software	2000 / XP / Vista	

#### Accessories

Battery, Instruction Manual, PC Interface Cable, Software, Instrument Lock.







## AAYUSH ELECTRICALS & INSTRUMENTATION ISO 9001-2015 CERTIFIED COMPANY

Web: <u>www.aayushei.com</u>, Mob: +91 88922 55555 / 96639 82272/ 88922 77777

Office Address: #1, 1st Main, 2nd Cross, Maruthinagar, Bengaluru, Karnataka - 560 026. India Factory Address: #18,4th A Main Road, Bahubali Nagar, Jahalli Village, Bengaluru - 560013 Email: sales@aayushei.com / marketing@aayushei.com / accounts@aayushei.com



