



DT-380

DIGITAL COMPACT AC CLAMP METER

The CEM DT-380 comes with all the rugged, reliable and accurate features you trust, in a small, ergonomic design. The innovative body design offers a more compact tool to meet your needs. With features of AC current measurements up to 400 A, a large 30 mm jaw opening and CAT III 600V safety rating, you get an easy-to-use tool that handles your everyday electrical maintenance needs.

The meter confirms to EN-61010-1, EN-61326. The instrument houses a Non-Contact Voltage Detector to show the presence of live wire. The Flashlight in the clamp jaw and the backlit display helps easy access in dark and tight areas.

FEATURES

- 3-1/2 Digits 1999 Counts Backlit LCD Display
- Non Contact Voltage Detector Built-in
- Flashlight in the clamp to access dark areas
- Single Hand Easy Operation
- Full Overload Protection
- Data Hold Function to Freeze the display
- AC Voltage & Current Bandwidth 50 to 60Hz
- Diode Test and Audible Continuity Test
- Low Battery and Overload Indication
- Temperature Measuring Facility with K type thermocouple
- AC/DC Voltage and AC Current measuring facility
- Resistance measurement
- Clamp Jaw Dia of 30mm
- Operating Temperature: 5 to 40°C (41°F to 104°F)
- Storage Temperature: -20 to 60°C (-4°F to 140°F)
- Operating Humidity: Max 80% up to 31°C decreasing linearly to 50% at 40°C
- Storage Humidity < 80% RH
- Operating Altitude 7000 ft
- 2 x 1.5V AAA Battery Operated
- Size: 230 x 82 x 40 mm / Weight: 230g.
- Safety: IEC 61010-1, CAT III 600V, CE

DT-380 | Digital Compact AC Clamp Meter

SPECIFICATIONS

Function	Range	Resolution	Accuracy
AC Current (50 to 60Hz)	20A	0.01A	$\pm (2.5 \% \pm 5 \text{ Digits})$
	200A	0.1A	
	400A	1A	$\pm (3.0 \% \pm 5 \text{ Digits})$

Function	Range	Resolution	Accuracy
DC Voltage	200mV	0.1mV	$\pm (1.5 \% \pm 2 \text{ Digits})$
	2V	0.001V	
	20V	0.01V	
	200V	0.1V	
	600V	1V	$\pm (2.0 \% \pm 2 \text{ Digits})$

Input Protection: 600V DC.

Function	Range	Resolution	Accuracy
AC Voltage (50Hz to 60Hz)	200mV	0.1mV	$\pm (1.5 \% \pm 10 \text{ Digits})$
	2V	0.001V	$\pm (1.5 \% \pm 8 \text{ Digits})$
	20V	0.01V	
	200V	0.1V	
	600V	1V	$\pm (2.5 \% \pm 8 \text{ Digits})$

Input Protection: 600V AC RMS.

Function	Range	Resolution	Accuracy
Resistance	200 Ω	0.1 Ω	$\pm (1.0 \% \pm 4 \text{ Digits})$
	2 K Ω	0.001 K Ω	$\pm (1.5 \% \pm 4 \text{ Digits})$
	20 K Ω	0.01 K Ω	
	200 K Ω	0.1 K Ω	
	2 M Ω	1 K Ω	$\pm (2.5 \% \pm 4 \text{ Digits})$
	20 M Ω	10 K Ω	$\pm (3.5 \% \pm 4 \text{ Digits})$

Input Protection: 250V DC or 250V AC RMS.

Function	Range	Resolution	Accuracy
Temperature (type-K) (probe accuracy not included)	-20 to 760°C	1°C	$\pm (3 \% \pm 5 \text{ Digits})$
	-4 to 1400°C	1°F	

Input Protection: 250V DC or 250V AC RMS.

Function	Testing Condition	Reading
Diode	Forward DCA is approx. 0.3mA, open circuit Voltage MAX . 1.5V	Forward voltage drop of Diode
Continuity	Open Voltage is approx 0.5V	Buzzer makes a long sound, While resistance is less than (50 Ω)

Input Protection: 250V DC or 250V AC RMS.

INCLUDED ACCESSORIES:

- Carrying Case
- Testing Leads
- Temperature Probe
- Battery
- Instruction Manual
- Test Certificate



AAYUSH ELECTRICALS & INSTRUMENTATION
ISO 9001-2015 CERTIFIED COMPANY

Office Address : # 1, 1st Main, 2nd Cross, Maruthinagar, Bengaluru, Karnataka - 560 026. India

Factory Address : #18 ,4th A Main Road, Bahubali Nagar, Jahalli Village, Bengaluru - 560013

Email : sales@aayushei.com / marketing@aayushei.com / accounts@aayushei.com

Web : www.aayushei.com , Mob : +91 88922 55555 / 96639 82272 / 88922 77777



QMS/019303/1120