







The most simple and easy to use voltage detector that is a must for all technicians. Not only does it measures and dectects voltage, it also determines phase rotation directions.

DT-9030

VOLTAGE TESTER

- I Auto Detection of AC/DC Voltage
- I Voltage measurement up to 400V AC/DC and 690V DC
- I Displays Direction of Phase Rotation
- I Low Impedance Test
- I Continuity Test

www.aayushei.com

DT-9030 Voltage Tester

General Specifications

LCD display	1999 counts (3 1/2 digit) LCD display with bargraph & backlight
Voltage range	6,12, 24, 50, 120, 230, 400V AC/DC, 690V DC
Resolution	1V AC/DC
Tolerances	DCV: +1.0% of reading +3 digit
	ACV: +1.5% of reading +5 digit
400VAC Max. measuring current	approx. ≤1.0mA
690VDC Max. measuring current	approx. ≤1.5mA
Voltage Detection	automatic
Polarity Detection	full range
Range Detection	automatic
Response Time	Updates 2~3 / sec.
ACV Frequency Range	50/60Hz
Internal Impedance	approx. ≤1MΩ
Operation Time	Long
LCD on	>4. 5V AC/DC
Single-pole Phase Test	
Voltage range:	100400V AC
ACV Frequency range	50/60Hz
Continuity Test	
Resistance range	<200kΩ
Test current	<1µA
Overvoltage protection	400V AC/690V DC
Rotary Field Indication	
Voltage range (LEDs)	100400V
Frequency range	50/60Hz
Measurement principle	double-pole and contact electrode
Low impedance test	
Voltage range	12~230VAC/DC
Low impedance	<6kΩ
Operation time	5s<250V AC/DC, ls< = 0.2A(690V)/30s max.
Overvoltage protection	3s<400V AC/690V DC
Power supply	2x1.5V "AAA" Batteries
Temperature range	-10°C up to + 55°C
Humidity	max.85% relative humidity
Overvoltage class	CATIII -690V AC/DC

Accessories

Batteries, Instruction Manual and Test Certificate.





QMS/019303/1120